

TAKEUCHI[®]

2018 MACHINE PRICE LIST

519 Bonnie Valentine Way, Pendergrass, GA 30567

e-mail sales@takeuchi-us.com
www.takeuchi-us.com

Prices and specifications
subject to change without notice

Prices are F.O.B. Pendergrass, GA
Effective 1 January 2018



TB210R

Compact Excavator

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel:706-693-3600 Fax:706-693-3725

www.takeuchi-us.com

STANDARD EQUIPMENT

| | |
|----------------------------------|--|
| Operating Weight: 2,370 lbs. | ROPS/TOPS 2 post foldable canopy |
| Width: 29.5" / 40.2" | Hydraulically retractable track frame |
| Maximum Dig Depth: 5' 9.1" | Adjustable width dozer blade with 2 pin-on extensions |
| Bucket Digging Force: 2,518 lbs. | Pilot operated joystick controls with safety lock out |
| Horsepower / RPM: 11.7 / 2,200 | Control pattern change valve |
| Travel Speed: 1.2 / 2.3 mph | Two-way auxiliary hydraulic circuit routed to the end of the arm |
| Auxiliary Flow: 5.8 gpm | Adjustable seat with 2" retractable seat belt |
| Boom swing: Left 85° / Right 85° | Two speed travel |
| 7.1" wide rubber tracks | Travel alarm |
| | Boom mounted work light |
| | Horn |
| | Cast iron, wrap around counterweight |

BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|--------------|--|----------------------|
| TB210R | TB210R Equipped with ROPS/TOPS 2-post foldable canopy, Rubber tracks, Travel alarm, Auxiliary hydraulics | \$24,750 |

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

| | | |
|----------|---|-------|
| BTB00708 | 8" Bucket with teeth, .8 cu. ft. capacity | \$360 |
| BTB00712 | 12" Bucket with teeth, 1.1 cu. ft. capacity | \$380 |

FIELD INSTALLED OPTIONS

| | | |
|------------|---|-------|
| 0333400003 | 3" Retractable seat belt in lieu of standard 2" | \$157 |
|------------|---|-------|

TAKEUCHI

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

TB216

Compact Excavator

STANDARD EQUIPMENT

| | |
|------------------------------------|---|
| Operating Weight: 3,902 lbs. | ROPS/TOPS/FOPS 4 post canopy |
| Width: 38.6" / 51.2" | LCD gauge panel with multi-functional operator information center |
| Maximum Dig Depth: 7' 9.1" | Hydraulically retractable track frame |
| Bucket Digging Force: 4,250 lbs. | Travel alarm |
| Horsepower / RPM: 15 / 2,400 | Two-speed travel with automatic down shift |
| Travel Speed: 1.4 / 2.6 mph | Control pattern selector valve |
| Auxiliary Flow: 8.9 gpm | Pilot operated joystick controls with safety lock out |
| Boom swing: Left 80°/ Right 50° | Cast iron, wrap around counterweight |
| 9" wide rubber tracks | Adjustable suspension seat with 2" retractable seat belt |
| Long Arm w/ integrated thumb mount | Two-way auxiliary hydraulic circuit routed to the end of the arm |
| | Variable displacement axial piston main hydraulic pumps |
| | Adjustable width dozer blade |
| | Electronic engine monitoring system |

BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|--------------|--|----------------------|
| TB216 | TB216 Equipped with ROPS/TOPS/FOPS canopy, Rubber tracks | \$32,526 |

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

| | | |
|-----------|--|---------|
| BTB01608 | 8" Pin-On Bucket with teeth, 1.1 cu. ft. capacity | \$465 |
| BTB01612 | 12" Pin-On Bucket with teeth, 1.5 cu. ft. capacity | \$480 |
| BTB01618 | 18" Pin-On Bucket with teeth, 2.4 cu. ft. capacity | \$557 |
| BTB01624 | 24" Pin-On Bucket with teeth, 3.2 cu. ft. capacity | \$650 |
| BQC01600 | Quick Coupler | \$785 |
| BQC01612 | 12" Quick Coupler Bucket with teeth, 1.5 cu. ft. capacity | \$480 |
| BQC01618 | 18" Quick Coupler Bucket with teeth, 2.4 cu. ft. capacity | \$557 |
| BQC01624 | 24" Quick Coupler Bucket with teeth, 3.2 cu. ft. capacity | \$650 |
| BQC01624D | 24" Quick Coupler Ditch Bucket, 3.0 cu. ft. capacity | \$882 |
| ATH216I | INSTALLED Hydraulic thumb (Only compatible w/ 12" or larger Buckets) | \$2,025 |

FIELD INSTALLED OPTIONS

| | | |
|------------|---|---------|
| 1914199048 | 3" Non-retractable seat belt in lieu of standard 2" | \$73 |
| ATH216K | Hydraulic thumb (Only compatible with 12" and larger buckets) | \$1,680 |

TAKEUCHI

519 Bonnie Valentine Way, Pendergrass, GA 30567

Tel:706-693-3600 Fax:706-693-3725

www.takeuchi-us.com

TB216H

Hybrid Compact Excavator

STANDARD EQUIPMENT

| | |
|---|---|
| Operating Weight: 4,277 lbs. | LCD gauge panel with multi-functional operator information center |
| Width: 38.6" / 51.2" | Hydraulically retractable track frame |
| Maximum Dig Depth: 7' 9.1" | Travel alarm |
| Bucket Digging Force: 4,250 lbs. | Two-speed travel with automatic down shift |
| Horsepower / RPM: 14.9 / 2,400 (diesel) | Control pattern selector valve |
| 14.2 / 2,400 (electric) | Pilot operated joystick controls with safety lock out |
| Travel Speed: 1.4 / 2.6 mph | Cast iron, wrap around counterweight |
| Auxiliary Flow: 8.9 gpm | Adjustable suspension seat with 2" retractable seat belt |
| Boom swing: Left 80°/ Right 50° | Two-way auxiliary hydraulic circuit routed to the end of the arm |
| 9" wide rubber tracks | Variable displacement axial piston main hydraulic pumps |
| Long Arm w/ integrated thumb mount | Adjustable width dozer blade |
| ROPS/TOPS/OPG Level 1, 4 post canopy | Electronic engine monitoring system |

BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|--------------|--|----------------------|
| TB216H | TB216 Equipped with ROPS/TOPS/OPG Level 1 canopy, Rubber tracks, diesel engine/electric motor, and 15' extension cable | \$52,260 |

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

| | | |
|-----------|--|---------|
| BTB01608 | 8" Pin-On Bucket with teeth, 1.1 cu. ft. capacity | \$465 |
| BTB01612 | 12" Pin-On Bucket with teeth, 1.5 cu. ft. capacity | \$480 |
| BTB01618 | 18" Pin-On Bucket with teeth, 2.4 cu. ft. capacity | \$557 |
| BTB01624 | 24" Pin-On Bucket with teeth, 3.2 cu. ft. capacity | \$650 |
| BQC01600 | Quick Coupler | \$785 |
| BQC01612 | 12" Quick Coupler Bucket with teeth, 1.5 cu. ft. capacity | \$480 |
| BQC01618 | 18" Quick Coupler Bucket with teeth, 2.4 cu. ft. capacity | \$557 |
| BQC01624 | 24" Quick Coupler Bucket with teeth, 3.2 cu. ft. capacity | \$650 |
| BQC01624D | 24" Quick Coupler Ditch Bucket, 3.0 cu. ft. capacity | \$882 |
| ATH216I | INSTALLED Hydraulic thumb (Only compatible w/ 12" or larger Buckets) | \$2,025 |

FIELD INSTALLED OPTIONS

| | | |
|------------|---|---------|
| 1914199048 | 3" Non-retractable seat belt in lieu of standard 2" | \$73 |
| ATH216K | Hydraulic thumb (Only compatible with 12" and larger buckets) | \$1,680 |

TAKEUCHI

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

TB230

Compact Excavator

STANDARD EQUIPMENT

| | |
|--|--|
| Operating Weight: 6,607 lbs. | TOPS/ROPS/FOPS 4 post canopy |
| Width: 4' 9" | Color gauge panel with multi-function operator information center |
| Maximum Dig Depth: 10' 2" | High back adjustable suspension seat |
| Bucket Digging Force: 6,471 lbs. | Pilot operated joystick control with control pattern change valve |
| Horsepower / RPM: 24.4 / 2,400 | EPA Final Tier 4 compliant engine with engine monitoring system |
| Travel Speed: 1.7 / 3.0 mph | Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door |
| Auxiliary Flow: 13.4 gpm | High capacity radiator and hydraulic oil cooler |
| Boom Swing: Left 80°/ Right 60° | Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system, proportional slide switch, one-way mode and continous detent mode |
| Track Width: 11.8" | Safety features include: TOPS/ROPS/FOPS 4 post canopy, travel alarm, retractable seat belt, control lockout, pilot accumulator, and lights |
| Two speed travel with automatic shift down | Varibale displacement axial piston pump |
| Reinforced arm w/ Integrated thumb mount | Auto Idle |
| Heavy duty dozer blade with float | |
| TFM hardware standard equipment, service included through the standard warranty period (sn 13000923 ~) | |

BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|------------------------|---|----------------------|
| TB230 | TB230 Canopy Equipped with Rubber Tracks | \$42,127 |
| TB230A (w/Angle Blade) | TB230 Canopy (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge | \$44,960 |

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

| | | |
|-----------|--|---------|
| BTB12512 | 12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity | \$650 |
| BTB12518 | 18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity | \$675 |
| BTB12524 | 24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity | \$835 |
| BQC12500 | Quick Coupler | \$785 |
| BQC12512 | 12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity | \$650 |
| BQC12513 | 13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity | \$675 |
| BQC12518 | 18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity | \$675 |
| BQC12524 | 24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity | \$835 |
| BQC12536D | 36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity | \$1,015 |
| ATH230I | INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets) | \$1,920 |

FIELD INSTALLED OPTIONS

| | | |
|------------|---|---------|
| 1914199948 | 3" Retractable seat belt in lieu of standard 2" | \$91 |
| ATH230K | Hydraulic thumb (Only compatible with 13" and larger buckets) | \$1,575 |

TAKEUCHI FLEET MANAGEMENT

| | | |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

* Added to the first 2 years that come standard



TB235-2

Compact Excavator

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

STANDARD EQUIPMENT

| | |
|--|--|
| Operating Weight: 7,251 lbs. | TOPS/ROPS/FOPS 4 post canopy |
| Width: 5' 2.2" | Color gauge panel with multi-function operator information center |
| Maximum Dig Depth: 10' 7.7" | High back adjustable suspension seat |
| Bucket Digging Force: 6,092 lbs. | Pilot operated joystick control with control pattern change valve |
| Horsepower / RPM: 24.4 / 2,400 | EPA Final Tier 4 compliant engine and engine monitoring system |
| Travel Speed: 1.7 / 2.8 mph | Self bleeding fuel system with ground level fuel fill, sight gauge and lockable doo |
| Auxiliary Flow: 15.8 gpm | Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system |
| Boom Swing: Left 76° / Right 58° | proportional slide switch, one-way mode and continous detent mode |
| Track width: 11.8" | Safety features include: TOPS/ROPS/FOPS 4 post canopy, travel alarm, retractable seat belt, control lockout, pilot accumulator, and lights |
| Two speed travel with automatic shift down | Varifiable displacement axial piston pump |
| Reinforced arm w/ Integrated thumb mount | Auto Idle |
| Heavy duty dozer blade with float | |
| TFM hardware standard equipment, service included through the standard warranty period | |

BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|-----------------------------|---|----------------------|
| TB235-2R | TB235-2 Canopy Equipped with Rubber Tracks | \$47,500 |
| TB235-2RA (w/Angle Blade) | TB235-2 Canopy (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge | \$50,590 |
| TB235-2CR | TB235-2 Cab Equipped with Rubber TOPS/ROPS/FOPS enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 5.7" color monitor, 12v power outlet | \$54,800 |
| TB235-2CRA (w/ Angle Blade) | TB235-2 Cab (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge | \$57,890 |

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

| | | |
|-----------|--|---------|
| BTB13512 | 12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity | \$650 |
| BTB13518 | 18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity | \$675 |
| BTB13524 | 24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity | \$835 |
| BQC13500 | Quick Coupler | \$785 |
| BQC12512 | 12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity | \$650 |
| BQC12513 | 13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity | \$675 |
| BQC12518 | 18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity | \$675 |
| BQC12524 | 24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity | \$835 |
| BQC12536D | 36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity | \$1,015 |
| ATH235-2I | INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets) | \$1,920 |

FIELD INSTALLED OPTIONS

| | | |
|------------|---|---------|
| 1914199948 | 3" Retractable seat belt in lieu of standard 2" | \$91 |
| ATH235-2K | Hydraulic thumb (Only compatible with 13" and larger buckets) | \$1,575 |

TAKEUCHI FLEET MANAGEMENT

| | | |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

* Added to the first 2 years that come standard



TB240

Compact Excavator

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel: 706-693-3600 Fax: 706-693-3725
 www.takeuchi-us.com

STANDARD EQUIPMENT

| | |
|---|--|
| Operating Weight: 8,289 lbs. | TOPS/ROPS/FOPS 4 post canopy |
| Width: 5' 8.5" | Color gauge panel with multi-function operator information center |
| Maximum Dig Depth: 11' 6" | High back adjustable suspension seat |
| Bucket Digging Force: 9,959 lbs. | Pilot operated joystick control with control pattern change valve |
| Horsepower / RPM: 35.8 / 2,200 | EPA Final Tier 4 compliant engine with DPF and engine monitoring system |
| Travel Speed: 1.7 / 3.0 mph | Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door |
| Auxiliary Flow: 17.1 gpm | Side by side industrial type radiator and hydraulic oil cooler |
| Boom Swing: Left 76° / Right 58° | Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system, proportional slide switch, one-way mode and continuous detent mode |
| Track width: 13.8" | Safety features include: TOPS/ROPS/FOPS 4 post canopy, travel alarm, retractable seat belt, control lockout, pilot accumulator, and lights |
| Two speed travel with automatic shift down | Variable displacement axial piston pump |
| Reinforced arm w/ Integrated thumb mount | Auto Idle |
| Heavy duty dozer blade with float | |
| TFM hardware standard equipment, service included through the standard warranty period (Canopy: sn 124001379~ / Cab: sn 124001483~) | |

BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|--------------------------|---|----------------------|
| TB240 | TB240 Canopy Equipped with Rubber or Steel Tracks | \$54,343 |
| TB240A (w/Angle Blade) | TB240 Canopy (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge | \$57,433 |
| TB240C | TB240 Cab Equipped with Rubber or Steel Tracks TOPS/ROPS/FOPS enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 5.7" color monitor, 12v power outlet | \$61,903 |
| TB240CA (w/ Angle Blade) | TB240 Cab (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge | \$64,993 |

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

| | | |
|-----------|--|---------|
| BTB13512 | 12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity | \$650 |
| BTB13518 | 18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity | \$675 |
| BTB13524 | 24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity | \$835 |
| BQC13500 | Quick Coupler | \$785 |
| BQC12512 | 12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity | \$650 |
| BQC12513 | 13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity | \$675 |
| BQC12518 | 18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity | \$675 |
| BQC12524 | 24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity | \$835 |
| BQC12536D | 36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity | \$1,015 |
| ATH240I | INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets) | \$1,920 |

FIELD INSTALLED OPTIONS

| | | |
|-------------|---|---------|
| 1914199948 | 3" Retractable seat belt in lieu of standard 2" | \$91 |
| ATH240K | Hydraulic thumb (Only compatible with 13" and larger buckets) | \$1,575 |
| 1914054391A | Bolt on rubber pads for TB240 steel track unit | \$3,480 |

TAKEUCHI FLEET MANAGEMENT

| | | |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

* Added to the first 2 years that come standard



519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

TB260

Compact Excavator

STANDARD EQUIPMENT

| | |
|---|--|
| Operating Weight: 12,180 lbs. | TOPS/ROPS/FOPS 4 post canopy |
| Width: 6' 6.7" | Color gauge panel with multi-function operator information center |
| Maximum Dig Depth: 12' 9.4" | Adjustable high back suspension seat |
| Bucket Digging Force: 12,756 lbs. | Pilot operated joystick control with control pattern change valve |
| Horsepower / RPM: 47.6 / 2,400 | Proportional slide switch control auxiliary hydraulics |
| Travel Speed: 1.7 / 3.0 mph | EPA Final Tier 4 Turbocharged engine with DPF and engine monitoring system |
| Primary Aux Flow: 27.0 gpm | Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door |
| Second Aux Flow: 11.6 gpm | Side by side radiator and hydraulic cooler |
| Boom Swing: Left 78°/ Right 55° | Variable Displacement axial piston pump |
| Track Width: 15.7" | Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch controls |
| Two speed travel with automatic shift down | Primary auxiliary continuous mode and one-way mode |
| Reinforced arm w/ Integrated thumb mount | Safety features include: TOPS/ROPS/FOPS 4 post Canopy, travel alarm, retractable seat belt, control lockout, pilot accumulator, mirrors and lights |
| Heavy duty dozer blade with float | |
| Auto Idle | |
| TFM hardware standard equipment, service included through the standard warranty period (Canopy: sn 1261001302~ / Cab: sn 1261001605~) | |

BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|--|---|----------------------|
| TB260 | TB260 Equipped with ROPS/TOPS/FOPS canopy, Rubber or Steel Tracks | \$71,807 |
| TB260A (w/Angle Blade) | TB260 Canopy (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge | \$74,897 |
| TB260L (w/ Segmented Rubber Tracks) | TB260 Canopy (above Equipped with Segmented Rubber Tracks) | \$76,957 |
| TB260LA (w/ Angle Blade & Segmented Rubber Tracks) | TB260 Canopy (above Equipped with Segmented Rubber Tracks) w/ Angle Blade , Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge | \$80,047 |
| TB260C | TB260 Cab Equipped with Rubber or Steel Tracks TOPS/ROPS/FOPS enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 5.7" color monitor, 12v power outlet | \$78,605 |
| TB260CA (w/Angle Blade) | TB260 Cab (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge | \$81,695 |
| TB260CL (w/ Segmented Rubber Tracks) | TB260 Cab (above Equipped with Segmented Rubber Tracks) | \$83,755 |
| TB260CLA (w/ Angle Blade & Segmented Rubber Tracks) | TB260 Cab (above Equipped with Segmented Rubber Tracks) w/ Angle Blade , Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge | \$86,845 |

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

| | | |
|-----------|--|---------|
| BTB26012 | 12" Pin-On Bucket with Teeth, 2.6 cu. ft. capacity | \$945 |
| BTB26018 | 18" Pin-On Bucket with Teeth, 3.7 cu. ft. capacity | \$1,000 |
| BTB26024 | 24" Pin-On Bucket with Teeth, 5.1 cu. ft. capacity | \$1,080 |
| BTB26036 | 36" Pin-On Bucket with Teeth, 7.6 cu. ft. capacity | \$1,340 |
| BQC26000 | Quick Coupler | \$800 |
| BQC14512 | 12" Quick Coupler Bucket with Teeth, 2.8 cu. ft. capacity | \$945 |
| BQC14518 | 18" Quick Coupler Bucket with Teeth, 4.2 cu. ft. capacity | \$1,000 |
| BQC14524 | 24" Quick Coupler Bucket with Teeth, 5.6 cu. ft. capacity | \$1,080 |
| BQC14536 | 36" Quick Coupler Bucket with Teeth, 8.3 cu. ft. capacity | \$1,340 |
| BQC14536D | 36" Quick Coupler Ditch Bucket, 7.4 cu. ft. capacity | \$1,283 |
| ATH260I | INSTALLED Hydraulic thumb (Only compatible w/ 18" or larger Buckets) | \$2,070 |

FIELD INSTALLED OPTIONS

| | | |
|------------|---|---------|
| 1914199948 | 3" Retractable seat belt in lieu of standard 2" | \$91 |
| ATH260K | Hydraulic Thumb (Only compatible with 18" and larger buckets) | \$1,722 |

TAKEUCHI FLEET MANAGEMENT

| | | |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

* Added to the first 2 years that come standard

Prices are F.O.B. Pendergrass, GA
 Effective 1 January 2018

Prices and specifications
 subject to change without notice

STANDARD EQUIPMENT

| | |
|---|--|
| Operating Weight: 18,780 lbs. Width: 7' 7" Maximum Dig Depth: 15' Bucket Digging Force: 16,565 lbs. Net Horsepower / RPM: 69.2 / 2,000 Travel Speed: 1.6 / 3.1 mph Auxiliary Flow: 26.4 gpm / 14.5 gpm Boom Swing: Left 70° / Right 60° Track Width: 17.7" Rubber / 21.7" Steel | ROPS/FOPS enclosed cab w/ air conditioner/heat, windshield wiper, 12v power outlet, and AM/FM/MP3 radio Color 5.7" gauge panel with multi-function operator information center 10-way adjustable high back suspension seat Pilot operated joystick control with control pattern change valve EPA Final Tier 4 turbocharged engine with DPF and engine monitoring system Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door Side by side radiator and hydraulic cooler Load sensing variable displacement hydraulic system Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch Primary auxiliary continuous mode and one-way mode Safety features include: ROPS/FOPS enclosed cab, large skylight with sun shade, travel alarm, retractable seat belt, control lockout, pilot accumulator, boom holding valve with lift alarm, mirrors and lights |
|---|--|

Two speed travel with automatic shift down
 Reinforced arm w/ Integrated thumb mount
 Heavy duty dozer blade with float
 Automatic track tensioner
 Auto Idle
 TFM hardware standard equipment, service included through the standard warranty period (sn 185102670 ~)

BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|--|--|----------------------|
| TB290C | TB290 Cab Equipped with Rubber or Steel Tracks | \$113,815 |
| TB290CA (w/ Angle Blade) | TB290 Cab (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge | \$119,995 |
| TB290CL (w/ Segmented Rubber Tracks) | TB290 Cab (above Equipped except with Segmented Rubber Tracks) | \$119,779 |
| TB290CLA (w/ Angle Blade & Segmented Rubber Tracks) | TB290 Cab (above Equipped except with Segmented Rubber Tracks) with Angle Blade , Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge | \$125,959 |

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

| | | |
|-----------|--|---------|
| BTB07018 | 18" Pin-On Bucket with teeth, 5.6 cu. ft. capacity | \$1,080 |
| BTB07024 | 24" Pin-On Bucket with teeth, 7.8 cu. ft. capacity | \$1,155 |
| BTB07036 | 36" Pin-On Bucket with teeth, 12.2 cu. ft. capacity | \$1,445 |
| BQC07000 | Quick Coupler | \$1,030 |
| BQC07018 | 18" Quick Coupler Bucket with teeth, 6.2 cu. ft. capacity | \$1,080 |
| BQC07024 | 24" Quick Coupler Bucket with teeth, 8.6 cu. ft. capacity | \$1,155 |
| BQC07036 | 36" Quick Coupler Bucket with teeth, 12.2 cu. ft. capacity | \$1,445 |
| BQC07036D | 36" Quick Coupler Ditch Bucket 11.5 cu. ft. capacity | \$1,420 |
| ATH290I | INSTALLED Hydraulic thumb (Only compatible w/ 18" or larger Buckets) | \$2,790 |

FIELD INSTALLED OPTIONS

| | | |
|------------|---|---------|
| 1914199948 | 3" Retractable seat belt in lieu of standard 2" | \$91 |
| ATH290K | Hydraulic thumb (Only compatible with 18" and larger buckets) | \$2,435 |

TAKEUCHI FLEET MANAGEMENT

| | | |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

* Added to the first 2 years that come standard

TAKEUCHI

TB280FR

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

Zero Swing Excavator

STANDARD EQUIPMENT

| | |
|---|--|
| Operating Weight: 19,077 lbs. Width: 7' 7" Maximum Dig Depth: 14' 11" Bucket Digging Force: 16,335 lbs. Horsepower / RPM: 69.2 / 2,000 Travel Speed: 1.6 / 3.1 mph Auxiliary Flow: 39 gpm / 15 gpm Boom swing: Left 30°/ Right 15° Track Width: 17.7" Side-to-Side (STS) offset boom system Two speed travel with automatic shift down Reinforced arm w/ Integrated thumb mount Heavy duty dozer blade with float Auto idle TFM hardware standard equipment, service included through the standard warranty period (sn 178500473 ~) | ROPS/FOPS enclosed cab w/ air conditioner/heat, windshield wiper, 12v power outlet and AM/FM/MP3 radio Tilt-up operator's platform Color 5.7" gauge panel with multi-function operator information center 10-way adjustable high back suspension seat Pilot operated joystick control with control pattern change valve EPA Final Tier 4 turbocharged engine with DPF and engine monitoring system Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door Side by side radiator and hydraulic cooler Variable displacement axial piston main hydraulic pumps Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch Primary auxiliary continuous mode and one-way mode Safety features include: ROPS/FOPS enclosed cab, large skylight with sun shade, travel alarm, retractable seat belt, control lockout, pilot accumulator, boom holding valve with lift alarm, mirrors and lights |
|---|--|

BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|---|--|----------------------|
| TB280FRC | TB280FR Cab Equipped with Rubber or Steel Tracks | \$117,420 |
| TB280FRCL (w/ Segmented Rubber Tracks) | TB280FR Cab Equipped with Segmented Rubber Tracks | \$123,384 |

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

| | | |
|-------------|--|---------|
| BTB07018 | 18" Pin-On Bucket with teeth, 5.6 cu. ft. capacity | \$1,080 |
| BTB07024 | 24" Pin-On Bucket with teeth, 7.8 cu. ft. capacity | \$1,155 |
| BTB07036 * | 36" Pin-On Bucket with teeth, 12.2 cu. ft. capacity | \$1,445 |
| BQC07000 | Quick Coupler | \$1,030 |
| BQC07018 | 18" Quick Coupler Bucket with teeth, 6.2 cu. ft. capacity | \$1,080 |
| BQC07024 | 24" Quick Coupler Bucket with teeth, 8.6 cu. ft. capacity | \$1,155 |
| BQC07036 * | 36" Quick Coupler Bucket with teeth, 12.2 cu. ft. capacity | \$1,445 |
| BQC07036D * | 36" Quick Coupler Ditch Bucket 11.5 cu. ft. capacity | \$1,420 |
| ATH280FRI | INSTALLED Hydraulic thumb (Only compatible w/ 18" or larger Buckets) | \$2,790 |

FIELD INSTALLED OPTIONS

| | | |
|-------------|--|---------|
| 1914199948 | 3" Retractable seat belt in lieu of standard 2" belt | \$91 |
| ATH280FRK * | Hydraulic thumb (Only compatible with 18" and larger buckets) | \$2,435 |

* **NOTE:** The Zero Swing front radius feature is only available for the standard bucket attachment (30" or smaller)

TAKEUCHI FLEET MANAGEMENT

| | | |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

* Added to the first 2 years that come standard



TB2150

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

Excavator

STANDARD EQUIPMENT

| | |
|--|---|
| Operating Weight: 34,480 lbs. (Rubber) | Factory installed cab with automatic climate control, AM/FM/MP3 radio, wiper |
| Dozer Blade Width: 8' 6" | Two speed travel with automatic shift down |
| Maximum Dig Depth: 17' 10.4" | Travel alarm |
| Bucket Digging Force: 22,190 lbs. | Arm & Boom holding valve with lift alarm |
| Tail Swing Radius: 6' 6.7" | Control pattern selector valve |
| Horsepower / RPM: 114 / 2,000 | Pilot operated joystick controls with safety lock out |
| EPA Final Tier 4 Compliant | Wrap around counterweight with towers |
| Travel Speed: 1.9 / 3.4 mph | Adjustable air suspension seat with retractable seat belt |
| Auxiliary Flow: (Primary) 59.0 gpm | Primary and Secondary two-way auxiliary hydraulic circuits routed to the end of the arm |
| Auxiliary Flow: (Secondary) 14.5 gpm | Proportional thumb wheel control of both auxiliary hydraulic circuits |
| Boom Swing: Left 75° / Right 55° | Electrohydraulic push button controls of auxiliary hydraulic circuit (Primary Only) |
| 24" Wide Steel Tracks | Variable displacement axial piston main hydraulic pumps |
| Optional: 20" Rubber Track | Multi function color monitor panel |
| Optional: 20" Segmented Rubber Tracks | Heavy duty dozer blade with Float |
| TFM hardware standard equipment, service included through the standard warranty period | |

BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|--|---|----------------------|
| TB2150 | TB2150 Equipped with CAB, Rubber or Steel Tracks, Dozer blade with float, Auto Air Conditioner/Heat, Defroster, Windshield wiper and washer, Control pattern selector valve, Travel alarm, Cab light, Auxiliary hydraulics (primary and secondary), Slide back front window, AM/FM/MP3 radio, Air Suspension seat, Engine monitoring system | \$170,000 |
| TB2150CL (w/ Segmented Rubber Tracks) | TB2150 Cab (above Equipped except with Segmented Rubber Tracks) | \$178,948 |

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

| | | |
|------------|--|---------|
| BMC1140 | Mechanical Coupler: Pin Grabber type with Pins (700 lbs) | \$5,130 |
| BTB114018 | 18" Pin-On Bucket (Capacity 0.41) (875 lbs) | \$2,745 |
| BTB114024 | 24" Pin-On Bucket (Capacity 0.57) (1025 lbs) | \$2,825 |
| BTB114030 | 30" Pin-On Bucket (Capacity 0.73) (1110 lbs) | \$3,385 |
| BTB114036 | 36" Pin-On Bucket (Capacity 0.89) (1295 lbs) | \$3,660 |
| BTB114042D | 42" Pin-On Ditching Bucket (Capacity 0.50) (695 lbs) | \$2,708 |
| BTB114048D | 48" Pin-On Ditching Bucket (Capacity 0.60) (800 lbs) | \$2,915 |
| BTB114054D | 54" Pin-On Ditching Bucket (Capacity 0.70) (900 lbs) | \$3,130 |
| BTB114060D | 60" Pin-On Ditching Bucket (Capacity 0.80) (970 lbs) | \$3,335 |
| BTH1140I | INSTALLED Hydraulic thumb (Compatible with 24" and larger PIN ON buckets Only) (835 lbs) | \$7,765 |
| BTH1140LI | INSTALLED Hydraulic thumb (Compatible with 24" and larger PIN ON buckets and Mechanical Coupler) | \$7,765 |

FIELD INSTALLED OPTIONS

| | | |
|---------------|--|---------|
| K1573400001 | 3" Retractable seat belt in lieu of standard 2" | \$123 |
| BTH1140K | Hydraulic thumb (Compatible with 24" and larger PIN ON buckets Only) (835 lbs) | \$7,305 |
| BTH1140LK | Hydraulic thumb (Compatible with 24" and larger PIN ON buckets and Mechanical Coupler) | \$7,305 |
| TB1140BKTPINS | Bucket Pin Kit (includes Hardware) | \$482 |

TAKEUCHI FLEET MANAGEMENT

| | | |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

* Added to the first 2 years that come standard



TL6

Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

STANDARD EQUIPMENT

| | |
|---|---|
| Operating Weight: 7480 lbs. | Radial boom design |
| Overall Width Without Bucket: 60" | ROPS/FOPS tilt-up operators compartment w/ rearview mirrors |
| Tipping Load (SAE 732) 5,269 lbs. | Back-up alarm, Top and rear windows |
| Rated Operating Capacity (ROC)(SAE J818): 1,841 lbs | Automatic fuel bleed system |
| Bucket Digging Force: 5,930 lbs. | Pilot operated joystick controls |
| Horsepower / RPM: 65.2 / 2700 | Universal quick attach mounting bracket |
| Travel Speed: 4 / 6mph | Suspension seat with retractable seatbelt |
| Auxiliary Flow: 17.8 gpm | One and two way auxiliary hydraulics |
| Ground Pressure: 4.8 psi | Electronic engine monitoring system |
| Maximum Lift Height to Bucket Pin: 9' 6" | Electrohydraulic push button controls of auxiliary hydraulic circuit |
| Reach Fully Raised: 1' 10" | Proportional slide switch control auxiliary hydraulics with detent function |
| Canopy/Cab height: 6' 5" | Hydraulic self-leveling bucket |
| | Flat face, pressure releasing Hydraulic Couplers |
| | Standard 14-pin connector with push button control |
| | Dual element air cleaner |
| | Push button boom float with detent |
| | Foot Throttle |

EPA Final Tier 4 Turbocharged Engine with DPF

TFM hardware standard equipment, service included through the standard warranty period

BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|--------------|---|----------------------|
| TL6R | TL6 with ROPS/FOPS Canopy, Rubber tracks | \$46,791 |
| TL6CR | TL6 with ROPS/FOPS Cab with Air Conditioning/Heat Defroster, Rubber Tracks, Hydraulic quick attach, Swing out door, AM/FM/MP3 Radio | \$52,213 |

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

ATTACHMENTS

| | | |
|---------|---|---------|
| BTL867 | 67" HD smooth dirt bucket with bolt-on edge, 14.0 cubic feet capacity | \$1,570 |
| BTL867T | 67" HD dirt bucket with 7 teeth, 14.0 cubic feet capacity | \$1,465 |
| BPL1200 | 7' six way dozer blade | \$6,325 |
| BTLPF48 | HD 48" pallet forks and frame | \$1,185 |

FIELD INSTALLED OPTIONS

| | | |
|------------|---|------|
| 1914199948 | 3" Retractable seat belt in lieu of standard 2' | \$91 |
|------------|---|------|

TAKEUCHI FLEET MANAGEMENT

| | | |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

* Added to the first 2 years that come standard



TL8

Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

STANDARD EQUIPMENT

| | |
|--|--|
| Operating Weight: 8,345 lbs. | Radial boom design |
| Overall Width Without Bucket:(12"/15" Tracks) 62"/ 65' | ROPS/FOPS tilt-up operators compartment w/ RH/LH rearview mirrors |
| Tipping Load (SAE 732) 6,020 lbs | Back-up alarm, Top and rear windows |
| Rated Operating Capacity (ROC)(SAE J818): 2,105 lbs | Automatic fuel bleed system |
| Bucket Digging Force: 6,834 lbs | Pilot operated joystick controls |
| Horsepower / RPM: 74.3 / 2,600 | Universal quick attach mounting bracke |
| Travel Speed: 4.5 / 6.8 mph | Six-way adjustable suspension seat with retractable seatbel |
| Auxiliary Flow: 18.4 gpm | One and two way auxiliary hydraulics |
| Ground Pressure: 4.4 psi | Electronic engine monitoring system |
| Maximum Lift Height to Bucket Pin: 9' 11" | Electrohydraulic push button controls of auxiliary hydraulic circui |
| Reach Fully Raised: 2' 4.7" | Proportional slide switch control auxiliary hydraulics with detent functio |
| Canopy/Cab height: 6' 11.9" / 7' 4" | Hydraulic self-leveling bucket |
| | Flat face, pressure releasing Hydraulic Couplers |
| | Standard 14-pin connector with push button contrc |
| EPA Final Tier 4 Turbocharged Engine with DPF | Dual element air cleaner with standard pre-cleaner |
| | Push button boom float with deten |
| | Foot Throttle |

TFM hardware standard equipment, service included through the standard warranty period (Canopy: sn 200803984~/Cab: sn 200803863-

BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|-----------------|---|----------------------|
| TL8RW | TL8 with ROPS/FOPS Canopy, 15" Rubber tracks | \$53,303 |
| TL8RWP (w/ PC) | TL8RW (above Equipped) with Pattern Control* | \$54,281 |
| TL8CRW | TL8 with ROPS/FOPS Cab with Air Conditioning/Heat Defroster, 15" Rubber Tracks, Hydraulic quick attach Roll up door | \$59,483 |
| TL8CRWP (w/ PC) | TL8CRW (above Equipped) with Pattern Control* | \$60,461 |
| <hr/> | | |
| TL8RN | TL8 with ROPS/FOPS Canopy, 12" Rubber tracks | \$52,816 |
| TL8RNP (w/ PC) | TL8RN (above Equipped) with Pattern Control* | \$53,795 |
| TL8CRN | TL8 with ROPS/FOPS Cab with Air Conditioning/Heat Defroster, 12" Rubber Tracks, Hydraulic quick attach Roll up door | \$58,996 |
| TL8CRNP (w/ PC) | TL8CRN (above Equipped) with Pattern Control* | \$59,975 |

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

* PC requires a minimum of 90 days delivery time for factory order

ATTACHMENTS

NOTE: 67" and 76" buckets work with both 12" / 15" Track's

| | | |
|--------------|---|---------|
| BTL867 | 67" HD smooth dirt bucket with bolt-on edge, 14.0 cubic feet capacity | \$1,570 |
| BTL867T | 67" HD dirt bucket with 7 teeth, 14.0 cubic feet capacity | \$1,465 |
| ABLU-72S-057 | 72" Low Profile Bucket - Smooth with Bolt on Cutting Edge | \$1,612 |
| ABLU-72T-057 | 72" Low Profile Bucket - Tooth | \$1,523 |
| BTL1076 | 76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity | \$2,040 |
| BTL1076T | 76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity | \$1,895 |
| BPL1200 | 7' six way dozer blade | \$6,325 |
| BTLPF48 | HD 48" pallet forks and frame | \$1,185 |
| K288547011 | Radio kit installed (AM/FM/MP3) | \$500 |
| K488342041 | 3-point 2" seat belt kit Installed (in lieu of standard 2") | \$190 |

FIELD INSTALLED OPTIONS

| | | |
|------------|---|---------|
| 1914199948 | 3" Retractable seat belt in lieu of standard 2" | \$91 |
| K48834204 | 3-point 2" seat belt kit in lieu of standard 2" | \$150 |
| K28833001 | Counter Weight Kit TL8 (350 lbs)(Increase ROC to 2,323 lb | \$900 |
| K488710000 | H pattern fixed control kit for TL8 | \$353 |
| K48837001 | TL8 hydraulic quick attach coupler kit (for Canopy unit | \$1,560 |
| K28854701 | Radio kit (AM/FM/MP3) | \$421 |
| 1903908050 | Active Power Control Kit (Field Kit) | \$300 |

TAKEUCHI FLEET MANAGEMENT

| | | |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription' | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription' | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription' | \$500 |

* Added to the first 2 years that come standarc



TL8

Track Loader

HIGH FLOW

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

STANDARD EQUIPMENT

| | |
|---|---|
| Operating Weight: 8,620 lbs. | Radial boom design |
| Overall Width Without Bucket (w/ 15" Tracks): 65" | ROPS/FOPS tilt-up operators compartment w/ RH/LH rearview mirrors |
| Tipping Load (SAE 732): 6,020 lbs. | Back-up alarm, Top and rear windows |
| Rated Operating Capacity (ROC)(SAE J818): 2,105 lbs | Automatic fuel bleed system |
| Bucket Digging Force: 6,834 lbs. | Pilot operated joystick controls |
| Horsepower / RPM: 74.3 / 2,600 | Universal quick attach mounting bracket |
| Travel Speed: 4.5 / 6.8 mph | Six-way adjustable suspension seat with retractable seatbelt |
| Auxiliary Flow: 18.4 gpm STD / 33 gpm HF | One and two way auxiliary hydraulics |
| Ground Pressure: 4.5 psi | Electronic engine monitoring system |
| Maximum Lift Height to Bucket Pin: 9' 11" | Electrohydraulic push button controls of auxiliary hydraulic circuit |
| Reach Fully Raised: 2' 4.7" | Proportional slide switch control auxiliary hydraulics with detent function |
| Cab height: 7' 4" | Hydraulic self-leveling bucket |
| 1/2" Lexan roll up door | 1/2" Flat face, pressure relieving Hydraulic Couplers |
| EPA Final Tier 4 turbocharged engine with DPF | Standard 14-pin connector with push button control |
| | Dual element air cleaner with standard pre-cleaner |
| | Push button boom float with detent |
| | Foot throttle |

TFM hardware standard equipment, service included through the standard warranty period (Cab: sn 200803863~)

BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|------------------|---|----------------------|
| TL8CRWH | TL8 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, 15" Rubber Tracks, Hydraulic quick attach, Lexan Roll up door and HIGH FLOW auxiliary hydraulics (33 gpm) | \$62,315 |
| TL8CRWHP (w/ PC) | TL8CRW (above Equipped) with Pattern Control* | \$63,294 |

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

* PC requires a minimum of 90 days delivery time for factory order

ATTACHMENTS

| | | |
|--------------|---|---------|
| BTL867 | 67" HD smooth dirt bucket with bolt-on edge, 14.0 cubic feet capacity | \$1,570 |
| BTL867T | 67" HD dirt bucket with 7 teeth, 14.0 cubic feet capacity | \$1,465 |
| ABLU-72S-057 | 72" Low Profile Bucket - Smooth with Bolt on Cutting Edge | \$1,612 |
| ABLU-72T-057 | 72" Low Profile Bucket -Tooth | \$1,523 |
| BTL1076 | 76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity | \$2,040 |
| BTL1076T | 76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity | \$1,895 |
| BPL1200 | 7' six way dozer blade | \$6,325 |
| BTLPF48 | HD 48" pallet forks and frame | \$1,185 |
| K288547011 | Radio kit installed (AM/FM/MP3) | \$500 |
| K488342041 | 3-point 2" seat belt kit Installed (in lieu of standard 2") | \$190 |

FIELD INSTALLED OPTIONS

| | | |
|------------|--|-------|
| 1914199948 | 3" Retractable seat belt in lieu of standard 2" | \$91 |
| K48834204 | 3-point 2" seat belt kit in lieu of standard 2" | \$150 |
| K28833001 | Counter Weight Kit TL8 (350 lbs)(Increase ROC to 2,323 lb) | \$900 |
| K488710000 | H pattern fixed control kit for TL8 | \$353 |
| K28854701 | Radio kit (AM/FM/MP3) | \$421 |
| 1903908050 | Active Power Control Kit (Field Kit) | \$300 |

TAKEUCHI FLEET MANAGEMENT

| | | |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

* Added to the first 2 years that come standard

Prices and specifications
 subject to change without notice

P-11-B
 Prices are in US Dollar

Prices are F.O.B. Pendergrass, GA
 Effective 1 January 2018



TL10V2

Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

STANDARD EQUIPMENT

| | |
|---|---|
| Operating Weight: 9,840 lbs. | Vertical boom design |
| Overall Width Without Bucket: 68.5" | Tilt-up operators compartment |
| Tipping Load (SAE 732) 7,205 lbs. | Electronic dial type throttle and foot throttle |
| Rated Operating Capacity (ROC)(SAE J818): 2,522 lbs | Back-up alarm |
| Bucket Digging Force: 6,534 lbs. | Top and rear windows |
| Horsepower / RPM: 74.3 / 2,600 | Automatic fuel bleed system |
| Travel Speed: 4.8 / 7.0 | Pilot operated joystick controls |
| Auxiliary Flow: 18.8 gpm | Universal quick attach mounting bracket |
| Ground Pressure: 5.0 PSI | Deluxe high back suspension seat with retractable seatbel |
| Maximum Lift Height to Bucket Pin: 10' 4.7" | One and two way auxiliary hydraulics |
| Reach Fully Raised: 37.4" | Electronic engine monitoring system |
| Canopy/Cab height: 7' 5.3" | Electrohydraulic push button controls of auxiliary hydraulic circui |
| Selectable working modes | Proportional thumb wheel control auxiliary hydraulics with detent functio |
| Front & rear LED working lights | Hydraulic self-leveling bucket |
| Level 1 ROPS/FOPS operator protection | Flat face, pressure relieving Hydraulic Couplers |
| Multi function color monitor | Standard 14-pin connector with push botton contro |
| Active power control power management system | Dual element air cleaner |
| | Push button boom float with deteni |

TFM hardware standard equipment, service included through the standard warranty period

BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|--------------------------|---|----------------------|
| TL10V2--R | TL10 with ROPS/FOPS Canopy, 15.7" Rubber tracks | \$65,100 |
| TL10V2-RR (w/ RC) | TL10R (above Equipped) with Ride Control* | \$65,800 |
| TL10V2-RP (w/ PC) | TL10R (above Equipped) with Pattern Control* | \$66,050 |
| TL10V2-RRP (w/ RC & PC) | TL10R (above Equipped) with Ride Control & Pattern Control* | \$66,750 |
| TL10V2-CR | TL10 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster 15.7" Rubber Tracks, Hydraulic quick attach, Roll up door, AM/FM/MP3 Radic | \$71,500 |
| TL10V2-CRR (w/ RC) | TL10CR (above Equipped) with Ride Control* | \$72,200 |
| TL10V2-CRP (w/ PC) | TL10CR (above Equipped) with Pattern Control* | \$72,450 |
| TL10V2-CRRP (w/ RC & PC) | TL10CR (above Equipped) with Ride Control & Pattern Control* | \$73,150 |

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

* PC & RC requires a minimum of 90 days delivery time for factory order

ATTACHMENTS / OPTIONS

| | | |
|----------|---|---------|
| BTL1076 | 76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity | \$2,040 |
| BTL1076T | 76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity | \$1,895 |
| BPL1200 | 7' six way dozer blade | \$6,325 |
| BTLPF48 | HD 48" pallet forks and frame | \$1,185 |

FIELD INSTALLED OPTIONS

| | | |
|-------------|--|---------|
| 19141-99948 | 3" retractable seat belt in lieu of standard 2" | \$91 |
| K48847001 | Hydraulic quick attach coupler kit (for Canopy unit) | \$1,980 |

TAKEUCHI FLEET MANAGEMENT

| | | |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

* Added to the first 2 years that come standarc



TL10V2

Track Loader

HIGH FLOW

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

STANDARD EQUIPMENT

| | |
|---|--|
| Operating Weight: 10,138 lbs. | Vertical boom design |
| Overall Width Without Bucket: 68.5" | Tilt-up operators compartment |
| Tipping Load (SAE 732) 7,205 lbs. | Electronic dial type throttle and foot throttle |
| Rated Operating Capacity (ROC)(SAE J818): 2,522 lbs | Back-up alarm |
| Bucket Digging Force: 6,534 lbs. | Top and rear windows |
| Horsepower / RPM: 74.3 / 2,600 | Automatic fuel bleed system |
| Travel Speed: 4.8 / 7.0 | Pilot operated joystick controls |
| Auxiliary Flow (SP1): 18.8 gpm STD / 32.8 gpm HF | Universal quick attach mounting bracket |
| Ground Pressure: 5.1 PSI | Deluxe high back suspension seat with retractable seatbelt |
| Maximum Lift Height to Bucket Pin: 10' 4.7" | One and two way auxiliary hydraulics |
| Reach Fully Raised: 37.4" | Electronic engine monitoring system |
| Canopy/Cab height: 7' 5.3" | Electrohydraulic push button controls of auxiliary hydraulic circuit |
| Front & rear LED working lights | Proportional thumb wheel control auxiliary hydraulics with detent function |
| Level 2 ROPS / FOPS operator protection | Hydraulic self-leveling bucket |
| Multi function color monitor | Flat face, pressure relieving Hydraulic Couplers |
| | Standard 14-pin connector with push button control |
| | Dual element air cleaner |
| | Push button boom float with detent |

TFM hardware standard equipment, service included through the standard warranty period

BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|---------------------------|--|----------------------|
| TL10V2-CRH | TL10 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, 15.7" Rubber Tracks, Hydraulic quick attach, Roll up Lexan door, AM/FM/MP3 Radio, HIGH FLOW Auxiliary Hydraulics w/ second auxillary line | \$74,550 |
| TL10V2-CRHR (w/ RC) | TL10CRH (above Equipped) with Ride Control* | \$75,250 |
| TL10V2-CRHP (w/ PC) | TL10CRH (above Equipped) with Pattern Control* | \$75,500 |
| TL10V2-CRHRP (w/ RC & PC) | TL10CRH (above Equipped) with Ride Control & Pattern Control* | \$76,200 |

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

* PC & RC requires a minimum of 90 days delivery time for factory order

ATTACHMENTS / OPTIONS

| | | |
|------------|---|---------|
| BTL1076 | 76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity | \$2,040 |
| BTL1076T | 76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity | \$1,895 |
| BPL1200 | 7' six way dozer blade | \$6,325 |
| BTLPF48 | HD 48" pallet forks and frame | \$1,185 |
| K28854204I | 3-point 2" seat belt kit Installed (in lieu of standard 2") | \$190 |

FIELD INSTALLED OPTIONS

| | | |
|-------------|---|------|
| 19141-99948 | 3" retractable seat belt in lieu of standard 2" | \$91 |
|-------------|---|------|

TAKEUCHI FLEET MANAGEMENT

| | | |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

* Added to the first 2 years that come standard



TL12R2

Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

STANDARD EQUIPMENT

| | |
|---|--|
| Operating Weight: 12,300 lbs. | Radial boom design |
| Overall Width Without Bucket: 77.2" | Tilt-up operators compartment |
| Tipping Load (SAE 732) 8,500 lbs. | Electronic dial type throttle and foot throttle |
| Rated Operating Capacity (ROC)(SAE J818): 2,975 lbs | Back-up alarm |
| Bucket Digging Force: 8,211 lbs. | Top and rear windows |
| Horsepower / RPM: 111.3 / 2,400 | Automatic fuel bleed system |
| Travel Speed: 5.0 / 7.8 mph | Pilot operated joystick controls |
| Auxiliary Flow: 23 gpm | Universal quick attach mounting bracket |
| Ground Pressure: 4.6 psi | Deluxe high back suspension seat with retractable seatbelt |
| Maximum Lift Height to Bucket Pin: 10' 6" | One and two way auxiliary hydraulics |
| Reach Fully Raised: 37.8" | Electronic engine monitoring system |
| Canopy/Cab height: 7' 7.9" | Electrohydraulic push button controls of auxiliary hydraulic circuit |
| Active power control power management system | Proportional thumb wheel control auxiliary hydraulics with detent function |
| Front & rear LED working lights | Hydraulic self-leveling bucket |
| Level 1 ROPS/FOPS operator protection | Flat face, pressure relieving Hydraulic Couplers |
| Multi function color monitor | Standard 14-pin connector with push button control |
| Selectable working modes | Dual element air cleaner |
| | Push button boom float with detent |

TFM hardware standard equipment, service included through the standard warranty period

BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|-------------------------|---|----------------------|
| TL12R2-R | TL12 with ROPS/FOPS Canopy, 17.7" Rubber tracks | \$80,500 |
| TL12R2-RR (w/ RC) | TL12R (above Equipped) with Ride Control* | \$81,200 |
| TL12R2-RP (w/ PC) | TL12R (above Equipped) with Pattern Control* | \$81,450 |
| TL12R2-RRP (w/ RC & PC) | TL12R (above Equipped) with Ride Control & Pattern Control* | \$82,150 |

| | | |
|--------------------------|---|----------|
| TL12R2-CR | TL12 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up door, AM/FM/MP3 Radio | \$87,050 |
| TL12R2-CRR (w/ RC) | TL12CR (above Equipped) with Ride Control* | \$87,750 |
| TL12R2-CRP (w/ PC) | TL12CR (above Equipped) with Pattern Control* | \$88,000 |
| TL12R2-CRRP (w/ RC & PC) | TL12CR (above Equipped) with Ride Control & Pattern Control* | \$88,700 |

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

* PC & RC requires a minimum of 90 days delivery time for factory order

ATTACHMENTS / OPTIONS

| | | |
|--------------|---|---------|
| BTL1280 | 80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity | \$2,270 |
| BTL1280T | 80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity | \$2,095 |
| ABLU-84S-100 | 84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu.ft. capacity | \$2,570 |
| ABLU-84T-100 | 84" High Capacity - HD Dirt Bucket - Tooth | \$2,472 |
| BPL12008 | 8' six way dozer blade | \$6,500 |
| BTLPF48 | HD 48" pallet forks and frame | \$1,185 |

FIELD INSTALLED OPTIONS

| | | |
|-------------|--|---------|
| 19141-99948 | 3" retractable seat belt in lieu of standard 2" | \$91 |
| 1914100145 | 3-point 2" seat belt kit in lieu of standard 2" | \$260 |
| K48867001 | Hydraulic quick attach coupler kit (for Canopy unit) | \$1,980 |

TAKEUCHI FLEET MANAGEMENT

| | | |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

* Added to the first 2 years that come standard

Prices and specifications
 subject to change without notice

P-13-A
 Prices are in US Dollar

Prices are F.O.B. Pendergrass, GA
 Effective 1 January 2018



TL12R2

Track Loader
HIGH FLOW

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel:706-693-3600 Fax:706-693-3725
www.takeuchi-us.com

STANDARD EQUIPMENT

| | |
|--|--|
| Operating Weight: 12,210 lbs. | Radial boom design |
| Overall Width Without Bucket: 77.2" | Tilt-up operators compartment |
| Tipping Load (SAE 732) 8,500 lbs. | Electronic dial type throttle and foot throttle |
| Rated Operating Capacity (ROC)(SAE J818): 2,975 lbs | Back-up alarm |
| Bucket Digging Force: 8,211 lbs. | Top and rear windows |
| Horsepower / RPM: 111.3 / 2,400 | Automatic fuel bleed system |
| Travel Speed: 5.0 / 7.8 mph | Pilot operated joystick controls |
| Auxiliary Flow (SP1): 23 gpm STD / 40 gpm HF | Universal quick attach mounting bracket |
| Auxiliary Flow (SP2): 23.1 gpm | Deluxe high back suspension seat with retractable seatbelt |
| Ground Pressure: 4.7 psi | One and two way auxiliary hydraulics |
| Maximum Lift Height to Bucket Pin: 10' 6" | Electronic engine monitoring system |
| Reach Fully Raised: 37.8" | Electrohydraulic push button controls of auxiliary hydraulic circuit |
| Cab height: 7' 7.9" | Proportional thumb wheel control auxiliary hydraulics with detent function |
| Active power control power management system | Hydraulic self-leveling bucket |
| Front & rear LED working lights | Flat face, pressure relieving Hydraulic Couplers |
| Level 2 ROPS / FOPS operator protection | Standard 14-pin connector with push button control |
| Multi function color monitor | Dual element air cleaner |
| Selectable working modes | Push button boom float with detent |
| TFM hardware standard equipment, service included through the standard warranty period | |

BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|---------------------------|--|----------------------|
| TL12R2-CRH | TL12 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up Lexan door, AM/FM/MP3 Radio, HIGH FLOW Auxiliary Hydraulics w/ second auxiliary line | \$90,050 |
| TL12R2-CRHR (w/ RC) | TL12CRH (above Equipped) with Ride Control* | \$90,750 |
| TL12R2-CRHP (w/ PC) | TL12CRH (above Equipped) with Pattern Control* | \$91,000 |
| TL12R2-CRHRP (w/ RC & PC) | TL12CRH (above Equipped) with Ride Control & Pattern Control* | \$91,700 |

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

* PC & RC requires a minimum of 90 days delivery time for factory order

ATTACHMENTS / OPTIONS

| | | |
|--------------|---|---------|
| BTL1280 | 80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity | \$2,270 |
| BTL1280T | 80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity | \$2,095 |
| ABLU-84S-100 | 84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu.ft. capacity | \$2,570 |
| ABLU-84T-100 | 84" High Capacity - HD Dirt Bucket - Tooth | \$2,472 |
| BPL12008 | 8' six way dozer blade | \$6,500 |
| BTLPF48 | HD 48" pallet forks and frame | \$1,185 |

FIELD INSTALLED OPTIONS

| | | |
|------------|---|-------|
| 1914199948 | 3" retractable seat belt in lieu of standard 2" | \$91 |
| 1914100145 | 3-point 2" seat belt kit in lieu of standard 2" | \$260 |

TAKEUCHI FLEET MANAGEMENT

| | | |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

* Added to the first 2 years that come standard



TL12V2

Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

STANDARD EQUIPMENT

| | |
|--|---|
| Operating Weight (Canopy/Cab): 12,860 lb / 13,040 lb | Vertical boom design |
| Overall Width Without Bucket: 77.2" | Tilt-up operators compartment |
| Tipping Load (SAE 732) 11,737 lbs. | Electronic dial type throttle and foot throttle |
| Rated Operating Capacity (ROC)(SAE J818): 4,107 lbs | Back-up alarm |
| Bucket Digging Force: 7,874 lbs. | Top and rear window |
| EPA Final Tie 4 with DOC + DPF + SCR | Automatic fuel bleed system |
| Horsepower / RPM: 111.3 / 2,400 | Pilot operated joystick controls |
| Travel Speed: 5.0 / 7.3 mph | Universal quick attach mounting bracket |
| Auxiliary Flow: 23.2 gpm | Deluxe high back suspension seat with retractable seatbelt |
| Ground Pressure (Canopy / Cab): 4.8 psi / 4.9 psi | One and two way auxiliary hydraulics |
| Maximum Lift Height to Bucket Pin: 10' 10" | Electronic engine monitoring system |
| Reach Fully Raised: 36.4" | Electrohydraulic push button controls of auxiliary hydraulic circuit |
| Canopy/Cab height: 7' 9.7" | Proportional slide switch control auxiliary hydraulics with detent function |
| Level 1 ROPS/FOPS operators protection | Hydraulic self-leveling bucket |
| Front & rear LED working lights | Flat face, pressure relieving hydraulic couplers |
| Selectable working modes | Standard 14-pin connector with push button control |
| Active power control power management system | Dual element air cleaner |
| Multi function color monitor | Push button boom float with detent |
| TFM hardware standard equipment, service included through the standard warranty period | |

BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|-------------------------|--|----------------------|
| TL12V2-R | TL12V with ROPS/FOPS Canopy, 17.7" Rubber tracks | \$83,500 |
| TL12V2-RR (w/ RC) | TL12VR (above Equipped) with Ride Control* | \$84,200 |
| TL12V2-RP (w/ PC) | TL12VR (above Equipped) with Pattern Control* | \$84,450 |
| TL12V2-RRP (w/ RC & PC) | TL12VR (above Equipped) with Ride Control & Pattern Control* | \$85,150 |

| | | |
|--------------------------|--|----------|
| TL12V2-CR | TL12V with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, AM/FM Radio, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up door | \$90,050 |
| TL12V2-CRR (w/ RC) | TL12VCR (above Equipped) with Ride Control* | \$90,750 |
| TL12V2-CRP (w/ PC) | TL12VCR (above Equipped) with Pattern Control* | \$91,000 |
| TL12V2-CRRP (w/ RC & PC) | TL12VCR (above Equipped) with Ride Control & Pattern Control* | \$91,700 |

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

* PC & RC requires a minimum of 90 days delivery time for factory order

ATTACHMENTS / OPTIONS

| | | |
|--------------|---|---------|
| BTL1280 | 80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity | \$2,270 |
| BTL1280T | 80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity | \$2,095 |
| ABLU-84S-100 | 84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu.ft. capacity | \$2,570 |
| ABLU-84T-100 | 84" High Capacity - HD Dirt Bucket - Tooth - 27 cu.ft. capacity | \$2,472 |
| BPL12008 | 8' six way dozer blade | \$6,500 |
| BTLPF48 | HD 48" pallet forks and frame | \$1,185 |

FIELD INSTALLED OPTIONS

| | | |
|------------|--|---------|
| 1914199948 | 3" retractable seat belt in lieu of standard 2" | \$91 |
| 1914100145 | 3-point 2" seat belt kit in lieu of standard 2" | \$260 |
| K48857001 | Hydraulic quick attach coupler kit (for Canopy unit) | \$1,980 |

TAKEUCHI FLEET MANAGEMENT

| | | |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

* Added to the first 2 years that come standard



TL12V2

Track Loader

HIGH FLOW

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

STANDARD EQUIPMENT

| | |
|--|---|
| Operating Weight: 13,040 lbs. | Vertical boom design |
| Overall Width Without Bucket: 77.2" | ROPS/FOPS tilt-up operators compartment |
| Tipping Load (SAE 732) 11,737 lbs. | Electronic dial type throttle and foot throttle |
| Rated Operating Capacity (ROC)(SAE J818): 4,107 lbs | Back-up alarm |
| Bucket Digging Force: 7,874 lbs. | Top and rear window |
| EPA Final Tier 4 with DOC + DPF + SCR | Automatic fuel bleed system |
| Horsepower / RPM: 111.3 / 2,400 | Pilot operated joystick controls |
| Travel Speed: 5.0 / 7.3 mph | Universal quick attach mounting bracket |
| Auxiliary Flow (Std / High Flow): 23.2 gpm / 40 gpm | Deluxe high back suspension seat with retractable seatbelt |
| Ground Pressure: 4.9 psi | One and two way auxiliary hydraulics |
| Maximum Lift Height to Bucket Pin: 10' 10" | Electronic engine monitoring system |
| Reach Fully Raised: 36.4" | Electrohydraulic push button controls of auxiliary hydraulic circuit |
| Cab height: 7' 9.7" | Proportional slide switch control auxiliary hydraulics with detent function |
| Level 2 ROPS/FOPS operators protection | Hydraulic self-leveling bucket |
| Front & rear LED working lights | Flat face, pressure relieving hydraulic couplers |
| Selectable working modes | Standard 14-pin connector with push button control |
| Active power control power management system | Dual element air cleaner |
| Multi function color monitor | Push button boom float with detent |
| TFM hardware standard equipment, service included through the standard warranty period | |

BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|---------------------------|--|----------------------|
| TL12V2-CRH | TL12 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, AM/FM Radio, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up Lexan door HIGH FLOW Auxiliary Hydraulics w/ second auxiliary line | \$93,050 |
| TL12V2-CRHR (w/ RC) | TL12VCRH (above Equipped) with Ride Control* | \$93,750 |
| TL12V2-CRHP (w/ PC) | TL12VCRH (above Equipped) with Pattern Control* | \$94,000 |
| TL12V2-CRHRP (w/ RC & PC) | TL12VCRH (above Equipped) with Ride Control & Pattern Control* | \$94,700 |

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

* PC & RC requires a minimum of 90 days delivery time for factory order

ATTACHMENTS / OPTIONS

| | | |
|--------------|---|---------|
| BTL1280 | 80" HD smooth dirt bucket with bolt-on edge, 24.0 cu.ft. capacity | \$2,270 |
| BTL1280T | 80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity | \$2,095 |
| ABLU-84S-100 | 84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu.ft. capacity | \$2,570 |
| ABLU-84T-100 | 84" High Capacity - HD Dirt Bucket - Tooth - 27 cu.ft. capacity | \$2,472 |
| BPL12008 | 8' six way dozer blade | \$6,500 |
| BTLPF48 | HD 48" pallet forks and frame | \$1,185 |

FIELD INSTALLED OPTIONS

| | | |
|------------|---|-------|
| 1914199948 | 3" retractable seat belt in lieu of standard 2" | \$91 |
| 1914100145 | 3-point 2" seat belt kit in lieu of standard 2" | \$260 |

TAKEUCHI FLEET MANAGEMENT

| | | |
|---------|--|-------|
| TFMS1YR | 1 Year Takeuchi Fleet Management Subscription* | \$180 |
| TFMS2YR | 2 Year Takeuchi Fleet Management Subscription* | \$340 |
| TFMS3YR | 3 Year Takeuchi Fleet Management Subscription* | \$500 |

* Added to the first 2 years that come standard



TW40

Wheel Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel:706-693-3600 Fax:706-693-3725
www.takeuchi-us.com

STANDARD EQUIPMENT

| | |
|---------------------------------------|--|
| Operating Weight: 7,275 lbs | Back-Up Alarm |
| Tip Load, Straight: 3,858 lbs | Front Working Lights |
| Bucket breakout force: 7,126 lbs | Rear Working Lights |
| HP / RPM: 39.4 hp / 2,800 rpm | Inching Pedal |
| Travel Speed (Max): 12.4 gpm | Front Limited Slip Axle 45% |
| Auxiliary Flow: 10.3 gpm | Auxiliary Hydraulic Lines |
| Maximum Height to Bucket pin: 9' 7.7" | Replaceable Bushings |
| Height: (Canopy) 8' / (Cab) 8' 2" | Bucket Float |
| Articulation: 40 /40 | Automatic Bucket Positioning |
| Lift Capacity @ G. L.: 5,260 lb | Heavy Duty Hydraulic SSL Style Quick Attach Coupler |
| Reach fully raised: 2' 8.5" | Center Pivot Steering |
| | Heavy Duty 31x15.5-15 Construction Tire Assembly |
| | Optional heated Cab features front/rear wiper and rear defrost |

BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|--------------|--|----------------------|
| TW40 | TW40 with Foldable ROPS Canopy and Tires | \$55,105 |
| TW40C | TW40 with Cab with Heat and Tires | \$59,740 |

BASE MACHINE PRICE DOES NOT INCLUDE ATTACHMENTS

ATTACHMENTS

| | | |
|----------|---|---------|
| BTW4060 | 60" General Purpose Bucket (0.66 cu. Yd) for TW40 with SSL Mount | \$2,300 |
| BTW4060A | 60" Bolt on Blade for BTW4060 | \$282 |
| BTW4060B | 60" Tooth Bar for BTW4060 (note: not compatible with bolt on blade) | \$643 |

FIELD INSTALLED OPTIONS

| | | |
|-------------|-----------------------|-------|
| TWFASTERKIT | TW Series Coupler Kit | \$132 |
|-------------|-----------------------|-------|



TW65

Wheel Loader

SERIES 2

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

STANDARD EQUIPMENT

| | |
|---|--|
| <p>Operating Weight: 11,354 lbs Tip Load, Straight: 9,171 lbs Bucket Breakout Force: 11,600 lbs HP / RPM: 73 / 2200 Travel Speed (Max): 12.4 mph Auxiliary Flow: 16.4 gpm Maximum Height to Bucket Pin: 10 ft 4.6 in Height: 8 ft 9.8 in Articulation: 40 /40 Lift Capacity @ G. L.: 10,319 lbs Reach Fully Raised: 24"</p> | <p>Enclosed cab w/ air conditioner, heat, front and rear windshield wiper, front and rear washer, rear window defrost LCD Gauge panel with multi-function operator information center with diagnostics and anti-theft capabilities Deluxe suspension seat Pilot operator loader joystick control EPA Final Tier 4 turbocharged engine with DOC and engine monitoring system Side by side radiator and hydraulic oil cooler Proportional thumb wheel control for auxiliary hydraulic circuit located in joystick 100% Front and rear differential lock Euro style attachment mount with hydraulic coupler Bucket float Mechanical bucket positioning Safety features include: ROPS/FOPS enclosed cab, back up alarm, lights retractable seatbelt, control lockout, and deluxe lighting package (front and rear working lights, front driving lights, front and rear hazard and directional indicators)</p> |
|---|--|

ORDER PROCEDURE

ORDER STEPS: 1. Choose base model 2. Choose Tire Option 3. Choose Attachments

BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|--------------|--|----------------------|
| TW65C2 | TW65 Cab | \$83,420 |
| TW65C2HS | TW65 Cab, High Speed Road Gear (24.8 mph max speed), & Ride Control | \$87,746 |
| TW65C2HF | TW65 Cab, High Flow Auxiliary Hydraulics (26 gpm) | \$88,271 |
| TW65C2HH | TW65 Cab, High Flow Auxiliary Hydraulics (26 gpm), High Speed Road Gear (24.8 mph max speed), & Ride Control | \$92,597 |

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET or TIRES

TIRE OPTION (BASE MACHINE DOES NOT INCLUDE TIRES)

| | | |
|-------------|---|---------|
| BTW65TIREHD | Heavy Duty Construction Tire Assy for TW65 / TW80 (4 x Tire Assy) | \$3,395 |
| BTW65TIREF | Floatation Tire Assy for TW65 / TW80 (4 x Tire Assy) | \$3,950 |

ATTACHMENTS

| | | |
|-----------|---|---------|
| BTW5077 | 77" Construction Combo Bucket (1.05 cu. Yd) for TW65/TW80 | \$2,310 |
| BTW5077A | 77" Bolt on Blade for BTW5077 | \$360 |
| BTW8082 | 81.5" General Purpose Bucket (1.3 cu. Yd) for TW80 | \$2,520 |
| BTW8082A | 82" Bolt-on Blade for BTW8082 | \$370 |
| BTWPF48 | 48" Combo Fork Assy for all TW's (Rated 8000 lb) | \$2,300 |
| BTWUNIADP | Combo Hitch to Universal SSL Adapter TW50/60/65/80 | \$2,200 |

FIELD INSTALLED OPTIONS

| | | |
|--------------|---|-------|
| 1914199948 | 3" Retractable seat belt in lieu of standard 2" | \$91 |
| TWFASTERKIT | TW Series Coupler Kit (Non Hig) | \$132 |
| TWCOUPLERKIT | TW Series Coupler Kit for HIGH FLOW UNITS ONLY | \$224 |



TW80

Wheel Loader

SERIES 2

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

STANDARD EQUIPMENT

| | |
|---|--|
| <p>Operating Weight: 12,700 lbs Tip Load, Straight: 10,065 lbs Bucket Breakout Force: 12,287 lbs HP / RPM: 73 / 2200 Travel Speed (Max): 12.4 mph Auxiliary Flow: 16.4 gpm Maximum Height to Bucket Pin: 11 ft 1 in Height: 8 ft 11.5 in Articulation: 40 /40 Lift Capacity @ G. L.: 12,287 lbs Reach Fully Raised: 29"</p> | <p>Enclosed cab w/ air conditioner, heat, front and rear windshield wiper, front and rear washer, rear window defrost LCD Gauge panel with multi-function operator information center with diagnostics and anti-theft capabilities Deluxe suspension seat Pilot operator loader joystick control EPA Final Tier 4 turbocharged engine with DOC and engine monitoring system Side by side radiator and hydraulic oil cooler Proportional thumb wheel control for auxiliary hydraulic circuit located in joystick 100% Front and rear differential lock Euro style attachment mount with hydraulic coupler Bucket float Mechanical bucket positioning Safety features include: ROPS/FOPS enclosed cab, back up alarm, lights retractable seatbelt, control lockout, and deluxe lighting package (front and rear working lights, front driving lights, front and rear hazard and directional indicators)</p> |
|---|--|

ORDER PROCEDURE

ORDER STEPS: 1. Choose base model 2. Choose Tire Option 3. Choose Attachments

BASE MACHINE WITH STANDARD EQUIPMENT

| Factory Code | Description | Suggested List Price |
|--------------|--|----------------------|
| TW80C2 | TW80 Cab | \$92,690 |
| TW80C2HS | TW80 Cab, High Speed Road Gear (24.8 mph max speed), & Ride Control | \$97,016 |
| TW80C2HF | TW80 Cab, High Flow Auxiliary Hydraulics (26 gpm) | \$97,541 |
| TW80C2HH | TW80 Cab, High Flow Auxiliary Hydraulics (26 gpm), High Speed Road Gear (24.8 mph max speed), & Ride Control | \$101,867 |

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET or TIRES

TIRE OPTION (BASE MACHINE DOES NOT INCLUDE TIRES)

| | | |
|-------------|---|---------|
| BTW65TIREHD | Heavy Duty Construction Tire Assy for TW65 / TW80 (4 x Tire Assy) | \$3,395 |
| BTW65TIREF | Floating Tire Assy for TW65 / TW80 (4 x Tire Assy) | \$3,950 |

ATTACHMENTS

| | | |
|-----------|--|---------|
| BTW8082 | 81.5" General Purpose Bucket (1.3 cu. Yd) for TW80 | \$2,520 |
| BTW8082A | 82" Bolt-on Blade for BTW8082 | \$370 |
| BTWPF48 | 48" Combo Fork Assy for all TW's (Rated 8000 lb) | \$2,300 |
| BTWUNIADP | Combo Hitch to Universal SSL Adapter TW50/60/65/80 | \$2,200 |

FIELD INSTALLED OPTIONS

| | | |
|--------------|---|-------|
| 1914199948 | 3" Retractable seat belt in lieu of standard 2" | \$91 |
| TWFASTERKIT | TW Series Coupler Kit | \$132 |
| TWCOUPLERKIT | TW Series Coupler Kit for HIGH FLOW UNITS ONLY | \$224 |



P3-Power Protection Plan + TFM*

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

Please visit the dealer portal for more detail on the Power Protection Plan or call the Pendergrass office.

* All P3 Extended warranties include the TFM monitoring service for models equipped with the TFM monitoring device.

Excavators

| | | | Model | TB210 | TB216 | TB216H | TB230 | TB235/2 | TB240 |
|------------|-------------------------|-------------|-------|-----------|-----------|------------|-----------|-----------|-----------|
| 2YR/2000HR | Full Machine | Item # | | n/a | n/a | n/a | n/a | n/a | n/a |
| 2YR/2000HR | Full Machine | List | | std | std | std | std | std | std |
| 3YR/3000HR | Power train | Item Number | | EW210P31 | EW216P31 | EW216HP31 | EW230P31 | EW235P31 | EW240P31 |
| 3YR/3000HR | Power train | List | | \$524 | \$628 | \$1,048 | \$844 | 948 | 1157 |
| 3YR/3000HR | Power Train & Hydraulic | Item Number | | EW210PH31 | EW216PH31 | EW216HPH31 | EW230PH31 | EW235PH31 | EW240PH31 |
| 3YR/3000HR | Power Train & Hydraulic | List | | \$874 | \$1,047 | \$1,747 | \$1,407 | 1581 | 1928 |
| 3YR/3000HR | Full Machine | Item Number | | EW210FM31 | EW216FM31 | EW216HPH31 | EW230FM31 | EW235FM31 | EW240FM31 |
| 3YR/3000HR | Full Machine | List | | \$1,092 | \$1,308 | \$2,184 | \$1,759 | 1976 | 2410 |
| 4YR/4000HR | Power train | Item Number | | EW210P41 | EW216P41 | EW216HP41 | EW230P41 | EW235P41 | EW240P41 |
| 4YR/4000HR | Power train | List | | \$1,223 | \$1,465 | \$2,446 | \$1,970 | 2213 | 2699 |
| 4YR/4000HR | Power Train & Hydraulic | Item Number | | EW210PH41 | EW216PH41 | EW216HPH41 | EW230PH41 | EW235PH41 | EW240PH41 |
| 4YR/4000HR | Power Train & Hydraulic | List | | \$1,878 | \$2,250 | \$3,756 | \$3,025 | 3399 | 4145 |
| 5YR/5000HR | Power train | Item Number | | EW210P51 | EW216P51 | EW216HP51 | EW230P51 | EW235P51 | EW240P51 |
| 5YR/5000HR | Power train | List | | \$1,398 | \$1,675 | \$2,796 | \$2,251 | 2529 | 3085 |
| 5YR/5000HR | Power Train & Hydraulic | Item Number | | EW210PH51 | EW216PH51 | EW216HPH51 | EW230PH51 | EW235PH51 | EW240PH51 |
| 5YR/5000HR | Power Train & Hydraulic | List | | \$2,140 | \$2,564 | \$4,281 | \$3,447 | 3873 | 4723 |

| | | | TB260 | TB290 | TB280FR | TB2150 |
|------------|-------------------|--------|-------|-----------|-----------|-----------|
| 2YR/2000HR | Full Machine | Item # | | n/a | n/a | n/a |
| 2YR/2000HR | Full Machine | List | | std | std | std |
| 3YR/3000HR | Power train | Item # | | EW260P31 | EW280P31 | EW290P31 |
| 3YR/3000HR | Power train | List | | \$1,572 | \$2,276 | \$2,147 |
| 3YR/3000HR | Power Train & Hyd | Item # | | EW260PH31 | EW280PH31 | EW290PH31 |
| 3YR/3000HR | Power Train & Hyd | List | | \$2,621 | \$3,794 | \$3,578 |
| 3YR/3000HR | Full Machine | Item # | | EW260FM31 | EW280FM31 | EW290FM31 |
| 3YR/3000HR | Full Machine | List | | \$3,276 | \$4,742 | \$4,472 |
| 4YR/4000HR | Power train | Item # | | EW260P41 | EW280P41 | EW290P41 |
| 4YR/4000HR | Power train | List | | \$3,669 | \$5,311 | \$5,009 |
| 4YR/4000HR | Power Train & Hyd | Item # | | EW260PH41 | EW280PH41 | EW290PH41 |
| 4YR/4000HR | Power Train & Hyd | List | | \$5,635 | \$8,157 | \$7,692 |
| 5YR/5000HR | Power train | Item # | | EW260P51 | EW280P51 | EW290P51 |
| 5YR/5000HR | Power train | List | | \$4,193 | \$6,070 | \$5,724 |
| 5YR/5000HR | Power Train & Hyd | Item # | | EW260PH51 | EW280PH51 | EW290PH51 |
| 5YR/5000HR | Power Train & Hyd | List | | \$6,421 | \$9,295 | \$8,765 |

For pricing on older models, please visit www.takeuchi-us.com under the P3 section



P3-Power Protection Plan + TFM*

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

Please visit the dealer portal for more detail on the Power Protection Plan or call the Pendergrass office.

* All P3 Extended warranties include the TFM monitoring service for models equipped with the TFM monitoring device.

Track Loaders

| | | | TL6 | TL8 | TL10V2 | TL12R2 | TL12V2 |
|------------|-------------------------|-------------|----------|----------|------------|------------|------------|
| 2YR/2000HR | Full Machine | Item_Number | n/a | n/a | n/a | n/a | n/a |
| 2YR/2000HR | Full Machine | List | std | std | std | std | std |
| 3YR/3000HR | Power train | Item_Number | EWL6P31 | EWL8P31 | EWL10VP31 | EWL12VP31 | EWL12VP31 |
| 3YR/3000HR | Power train | List | \$849 | \$1,033 | \$1,498 | \$1,947 | \$1,947 |
| 3YR/3000HR | Power Train & Hydraulic | Item_Number | EWL6PH31 | EWL8PH31 | EWL10VPH31 | EWL12VPH31 | EWL12VPH31 |
| 3YR/3000HR | Power Train & Hydraulic | List | \$1,414 | \$1,722 | \$2,496 | \$3,245 | \$3,245 |
| 3YR/3000HR | Full Machine | Item_Number | EWL6FM31 | EWL8FM31 | EWL10VFM31 | EWL12VFM31 | EWL12VFM31 |
| 3YR/3000HR | Full Machine | List | \$1,768 | \$2,153 | \$3,120 | \$4,056 | \$4,056 |
| 4YR/4000HR | Power train | Item_Number | EWL6P41 | EWL8P41 | EWL10VP41 | EWL12VP41 | EWL12VP41 |
| 4YR/4000HR | Power train | List | \$1,980 | \$2,411 | \$3,494 | \$4,543 | \$4,543 |
| 4YR/4000HR | Power Train & Hydraulic | Item_Number | EWL6PH41 | EWL8PH41 | EWL10VPH41 | EWL12VPH41 | EWL12VPH41 |
| 4YR/4000HR | Power Train & Hydraulic | List | \$3,041 | \$3,703 | \$5,366 | \$6,976 | \$6,976 |
| 5YR/5000HR | Power train | Item_Number | EWL6P51 | EWL8P51 | EWL10VP51 | EWL12VP51 | EWL12VP51 |
| 5YR/5000HR | Power train | List | \$2,263 | \$2,756 | \$3,994 | \$5,192 | \$5,192 |
| 5YR/5000HR | Power Train & Hydraulic | Item_Number | EWL6PH51 | EWL8PH51 | EWL10VPH51 | EWL12VPH51 | EWL12VPH51 |
| 5YR/5000HR | Power Train & Hydraulic | List | \$3,465 | \$4,219 | \$6,115 | \$7,950 | \$7,950 |

For pricing on older models, please visit www.takeuchi-us.com under the P3 section



P3-Power Protection Plan + TFM*

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

Please visit the dealer portal for more detail on the Power Protection Plan or call the Pendergrass office.

* All P3 Extended warranties include the TFM monitoring service for models equipped with the TFM monitoring device.

Wheel Loaders

| | | | TW 40 | TW 65 | TW80 |
|------------|-------------------------|-------------|----------|----------|----------|
| 2YR/2000HR | Full Machine | Item_Number | n/a | n/a | n/a |
| 2YR/2000HR | Full Machine | List | std | std | std |
| 3YR/3000HR | Power train | Item_Number | EW40P32 | EW65P32 | EW80P32 |
| 3YR/3000HR | Power train | List | \$1,068 | \$1,483 | \$1,687 |
| 3YR/3000HR | Power Train & Hydraulic | Item_Number | EW40PH32 | EW65PH32 | EW80PH32 |
| 3YR/3000HR | Power Train & Hydraulic | List | \$1,780 | \$2,471 | \$2,829 |
| 3YR/3000HR | Full Machine | Item_Number | EW40FM32 | EW65FM32 | EW80FM32 |
| 3YR/3000HR | Full Machine | List | \$2,226 | \$3,089 | \$3,536 |
| 4YR/4000HR | Power train | Item_Number | EW40P42 | EW65P42 | EW80P42 |
| 4YR/4000HR | Power train | List | \$2,493 | \$3,459 | \$3,960 |
| 4YR/4000HR | Power Train & Hydraulic | Item_Number | EW40PH42 | EW65PH42 | EW80PH42 |
| 4YR/4000HR | Power Train & Hydraulic | List | \$3,828 | \$5,313 | \$6,082 |
| 5YR/5000HR | Power train | Item_Number | EW40P52 | EW65P52 | EW80P52 |
| 5YR/5000HR | Power train | List | \$2,849 | \$3,954 | \$4,526 |
| 5YR/5000HR | Power Train & Hydraulic | Item_Number | EW40PH52 | EW65PH52 | EW80PH52 |
| 5YR/5000HR | Power Train & Hydraulic | List | \$4,362 | \$6,054 | \$6,931 |

For pricing on older models, please visit www.takeuchi-us.com under the P3 section